

**1 Identification of the substance and manufacturer**

**Trade name:** KIM-SEAL WEATHERPROOFING SEALANT CLEAR  
**Product code:** 80685  
**Product category:** PC9a Paints and coatings.  
**Manufacturer/Supplier:** Kimball Midwest  
 4800 Roberts Road  
 Columbus, OH 43228  
 800-233-1294  
 www.kimballmidwest.com  
**Emergency telephone number:** ChemTrec: 800-424-9300

**2 Hazard(s) identification****Classification of the substance or mixture**

Flam. Aerosol 1 H222 Extremely flammable aerosol.  
 Press. Gas H280 Contains gas under pressure; may explode if heated.  
 Repr. 2 H361 Suspected of damaging fertility or the unborn child.  
 STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.  
 Skin Irrit. 2 H315 Causes skin irritation.  
 Eye Irrit. 2A H319 Causes serious eye irritation.  
 STOT SE 3 H336 May cause drowsiness or dizziness.

**GHS Hazard pictograms**

GHS02 GHS04 GHS07 GHS08

**Signal word****Hazard statements**

Danger

Extremely flammable aerosol.  
 Contains gas under pressure; may explode if heated.  
 Causes skin irritation.  
 Causes serious eye irritation.  
 Suspected of damaging fertility or the unborn child.  
 May cause drowsiness or dizziness.

**Precautionary statements**

May cause damage to organs through prolonged or repeated exposure.  
 Obtain special instructions before use.  
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
 Do not spray on an open flame or other ignition source.  
 Pressurized container: Do not pierce or burn, even after use.  
 Wash hands thoroughly after handling.  
 Use only outdoors or in a well-ventilated area.  
 Do not handle until all safety precautions have been read and understood.  
 Wear protective gloves/protective clothing/eye protection/face protection.  
 Do not breathe dust/fume/gas/mist/vapors/spray.  
 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 Call a poison center/doctor if you feel unwell.  
 If skin irritation occurs: Get medical advice/attention.  
 If on skin: Wash with plenty of water.  
 Take off contaminated clothing and wash before reuse.  
 Store locked up.  
 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.  
 Store in a well-ventilated place. Keep container tightly closed.  
 Dispose of contents/container in accordance with local/regional/national/international regulations.

**3 Composition/information on ingredients****Chemical characterization: Mixtures**

**Chemical Description:** This product is a mixture of the substances listed below with nonhazardous additions.

**Dangerous components:**

|            |                                         |        |
|------------|-----------------------------------------|--------|
| 67-64-1    | Acetone                                 | 18.7%  |
| 108-88-3   | Toluene                                 | 18.12% |
| 74-98-6    | propane                                 | 11.33% |
| 64742-89-8 | VM&P Naphtha                            | 11.13% |
| 142-82-5   | heptane                                 | 8.23%  |
| 106-97-8   | n-butane                                | 6.66%  |
| 64742-47-8 | Mineral Spirits                         | 6.18%  |
| 64742-48-9 | Naphtha (petroleum), hydrotreated heavy | 1.92%  |
| 64742-94-5 | Solvent naptha, heavy aromatic          | 1.77%  |

**4 First-aid measures****After inhalation:****After skin contact:****After eye contact:****After swallowing:****Most important symptoms and effects:**

Supply fresh air; consult doctor in case of complaints.  
 Immediately wash with water and soap and rinse thoroughly.  
 Remove contaminated clothing. Wash exposed area with soap and water.  
 Rinse opened eye for several minutes under running water. Then consult a doctor.  
 Rinse out mouth and then drink plenty of water.  
 Rinse mouth with water. Do not induce vomiting.

Dizziness

## Safety Data Sheet

Printing date 11/12/2014

Revised On 11/12/2014

Trade name: CLEAR

Indication of any immediate medical attention needed:

No further relevant information available.

(Contd. of page 1)

**5 Fire-fighting measures****Extinguishing agents:**CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray.**Special hazards:**

Can form explosive gas-air mixtures.

**Protective equipment for firefighters:**

A respiratory protective device may be necessary.

**6 Accidental release measures****Personal precautions, protective equipment and emergency procedures:**

Use respiratory protective device against the effects of fumes/dust/aerosol.

**Methods and material for containment and cleaning up:**

Dispose contaminated material as waste according to section 13.

**7 Handling and storage****Precautions for safe handling**

Use only in well ventilated areas.

**Storage requirements:**

Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions. Store locked up.

**8 Exposure controls/personal protection****Components with limit values that require monitoring at the workplace:****67-64-1 Acetone**PEL (USA) Long-term value: 2400 mg/m<sup>3</sup>, 1000 ppmREL (USA) Long-term value: 590 mg/m<sup>3</sup>, 250 ppmTLV (USA) Short-term value: (1782) NIC-1187 mg/m<sup>3</sup>, (750) NIC-500 ppm  
Long-term value: (1188) NIC-594 mg/m<sup>3</sup>, (500) NIC-250 ppm  
BEI**108-88-3 Toluene**PEL (USA) Long-term value: 200 ppm  
Ceiling limit value: 300; 500\* ppm  
\*10-min peak per 8-hr shiftREL (USA) Short-term value: 560 mg/m<sup>3</sup>, 150 ppm  
Long-term value: 375 mg/m<sup>3</sup>, 100 ppmTLV (USA) Long-term value: 75 mg/m<sup>3</sup>, 20 ppm  
BEI**74-98-6 propane**PEL (USA) Long-term value: 1800 mg/m<sup>3</sup>, 1000 ppmREL (USA) Long-term value: 1800 mg/m<sup>3</sup>, 1000 ppm

TLV (USA) refer to Appendix F

**142-82-5 heptane**PEL (USA) Long-term value: 2000 mg/m<sup>3</sup>, 500 ppmREL (USA) Long-term value: 350 mg/m<sup>3</sup>, 85 ppm  
Ceiling limit value: 1800\* mg/m<sup>3</sup>, 440\* ppm  
\*15-minTLV (USA) Short-term value: 2050 mg/m<sup>3</sup>, 500 ppm  
Long-term value: 1640 mg/m<sup>3</sup>, 400 ppm**106-97-8 n-butane**REL (USA) Long-term value: 1900 mg/m<sup>3</sup>, 800 ppmTLV (USA) Short-term value: 2370 mg/m<sup>3</sup>, 1000 ppm**Ingredients with biological limit values:****67-64-1 Acetone**BEI (USA) 50 mg/L  
Medium: urine  
Time: end of shift  
Parameter: Acetone (nonspecific)**108-88-3 Toluene**BEI (USA) 0.02 mg/L  
Medium: blood  
Time: prior to last shift of workweek  
Parameter: Toluene0.03 mg/L  
Medium: urine  
Time: end of shift  
Parameter: Toluene0.3 mg/g creatinine  
Medium: urine  
Time: end of shift  
Parameter: o-Cresol with hydrolysis (background)**Hygienic protection:**

Immediately remove all soiled and contaminated clothing.

(Contd. on page 3)

## Safety Data Sheet

Printing date 11/12/2014

Revised On 11/12/2014

Trade name: CLEAR

(Contd. of page 2)

**Breathing equipment:**

Wash hands after use.  
 Avoid contact with the skin.  
 Avoid contact with the eyes and skin.  
 Do not eat or drink while working.  
 A respirator is generally not necessary when using this product outdoors or in large open areas.  
 In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygiene.

**Hand protection:****Eye protection:**

Protective gloves. The glove material must be impermeable and resistant to the substance.  
 Tightly sealed goggles

**9 Physical and chemical properties**

**Appearance:** Aerosol.  
**Odor:** Aromatic  
**Odor threshold:** Not determined.  
**pH-value:** Not determined.  
**Melting point/Melting range** Undetermined.  
**Boiling point:** -110 °C (-166 °F)  
**Flash point:** -19 °C (-2 °F)  
**Flammability (solid, gas):** Extremely flammable.  
**Decomposition temperature:** Not determined.  
**Auto igniting:** Product is not self-igniting.  
**Danger of explosion:** In use, may form flammable/explosive vapour-air mixture.  
**Lower Explosion Limit:** 1.7 Vol %  
**Upper Explosion Limit:** 10.9 Vol %  
**Vapor pressure:** Not determined.  
**Relative Density:** Between 0.77 and 0.85 (Water equals 1.00)  
**Vapour density** Not determined.  
**Evaporation rate** Not applicable.  
**Partition coefficient: n-octonal/water:** Not determined.  
**Solubility:** Not determined.  
**Viscosity:** Not determined.  
**VOC content:** 597.1 g/l / 4.98 lb/gl  
**VOC content (less exempt solvents):** 66.3 %  
**MIR Value:** 1.46  
**Solids content:** 14.9 %

**10 Stability and reactivity**

**Reactivity:** Stable at normal temperatures.  
**Conditions to avoid:** Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing temperatures.  
**Chemical stability:** Not fully evaluated.  
**Possibility of hazardous reactions:** No dangerous reactions known.  
**Incompatible materials:** No further relevant information available.  
**Hazardous decomposition:** No dangerous decomposition products known.

**11 Toxicological information****LD/LC50 values that are relevant for classification:****106-97-8 n-butane**

Inhalative LC50/4 h 658 mg/l (rat)

**64742-48-9 Naphtha (petroleum), hydrotreated heavy**

Oral LD50 &gt;5000 mg/kg (rat)

Dermal LD50 &gt;3000 mg/kg (rab)

**Information on toxicological effects:** No data available.**Sensitization:** No sensitizing effects known.**Carcinogenic categories****IARC (International Agency for Research on Cancer)**

108-88-3 Toluene

3

**NTP (National Toxicology Program)**

None of the ingredients is listed.

**12 Ecological information**

**Aquatic toxicity:** Hazardous for water, do not empty into drains.  
**Persistence and degradability:** The product is degradable after prolonged exposure to natural weathering processes.  
**Bioaccumulative potential:** No further relevant information available.  
**Mobility in soil:** No further relevant information available.  
**Other adverse effects:** No further relevant information available.

(Contd. on page 4)

## Safety Data Sheet

Printing date 11/12/2014

Revised On 11/12/2014

Trade name: CLEAR

(Contd. of page 3)

**13 Disposal considerations**

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

**Recommendation:** Completely empty cans should be recycled.

**14 Transport information**

|                               |                                          |
|-------------------------------|------------------------------------------|
| UN-Number                     | UN1950                                   |
| DOT                           | Aerosols, flammable                      |
| ADR                           | 1950 Aerosols, ENVIRONMENTALLY HAZARDOUS |
| Transport hazard class(es):   |                                          |
| Class                         | 2.1                                      |
| Marine pollutant:             | Yes                                      |
|                               | Symbol (fish and tree)                   |
| Special marking (ADR):        | Symbol (fish and tree)                   |
| Special precautions for user: | Warning: Gases                           |
| EMS Number:                   | F-D,S-U                                  |
| Packaging Group:              | --                                       |
| UN "Model Regulation":        | UN1950, Aerosols, 2.1                    |

**15 Regulatory information****SARA Section 355 (extremely hazardous substances):**

None of the ingredients in this product are listed.

**SARA Section 313 (Specific toxic chemical listings):**

|          |         |
|----------|---------|
| 108-88-3 | Toluene |
|----------|---------|

**CPSC:** This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

**California Proposition 65 chemicals known to cause cancer:**

None of the ingredients in this product are listed.

**California Proposition 65 chemicals known to cause developmental toxicity:**

|  |                  |
|--|------------------|
|  | 108-88-3 Toluene |
|--|------------------|

**CANADIAN ENVIRONMENTAL PROTECTION ACT:**

All hazardous ingredients for this product appear on the Canadian Domestic Substance List.

**EPA:**

|          |         |    |
|----------|---------|----|
| 67-64-1  | Acetone | I  |
| 108-88-3 | Toluene | II |
| 142-82-5 | heptane | D  |

**16 Other information**

|                                            |                    |
|--------------------------------------------|--------------------|
| <b>Contact:</b>                            | Regulatory Affairs |
| <b>Date of preparation / last revision</b> | 11/12/2014 / -     |