

# Safety Data Sheet

acc. to OSHA HCS

Printing date 10/13/2014

Revised On 10/13/2014

## 1 Identification of the substance and manufacturer

**Trade name:** TRAFFIC MARKING PAINT - TRAFFIC WHITE  
**Product code:** 80892  
**Product category:** PC9a Paints and coatings.  
**Manufacturer/Supplier:** Kimball Midwest  
 4800 Roberts Road  
 Columbus, OH 43228  
 800-233-1294  
 www.kimballmidwest.com  
 ChemTrec: 800-424-9300

**Emergency telephone number:**



## 2 Hazard(s) identification

### Classification of the substance or mixture

Flam. Aerosol 1 H222 Extremely flammable aerosol.  
 Press. Gas H280 Contains gas under pressure; may explode if heated.  
 Carc. 2 H351 Suspected of causing cancer.  
 STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.  
 Eye Irrit. 2A H319 Causes serious eye irritation.

### GHS Hazard pictograms



GHS02 GHS04 GHS07 GHS08

### Signal word Hazard statements

**Signal word:** Danger  
**Hazard statements:** Extremely flammable aerosol.  
 Contains gas under pressure; may explode if heated.  
 Causes serious eye irritation.  
 Suspected of causing cancer.

### Precautionary statements

May cause damage to organs through prolonged or repeated exposure.  
 Obtain special instructions before use.  
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
 Do not spray on an open flame or other ignition source.  
 Pressurized container: Do not pierce or burn, even after use.  
 Wash hands thoroughly after handling.  
 Do not handle until all safety precautions have been read and understood.  
 Wear protective gloves/protective clothing/eye protection/face protection.  
 Do not breathe dust/fume/gas/mist/vapors/spray.  
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 If eye irritation persists: Get medical advice/attention.  
 Store locked up.  
 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.  
 Store in a well-ventilated place.  
 Dispose of contents/container in accordance with local/regional/national/international regulations.

## 3 Composition/information on ingredients

### Chemical characterization: Mixtures

**Chemical Description:** This product is a mixture of the substances listed below with nonhazardous additions.

#### Dangerous components:

|            |                          |        |
|------------|--------------------------|--------|
| 64742-89-8 | VM&P Naphtha             | 24.36% |
| 74-98-6    | propane                  | 12.6%  |
| 13463-67-7 | titanium dioxide         | 8.28%  |
| 106-97-8   | n-butane                 | 7.4%   |
| 7727-43-7  | barium sulphate, natural | 5.77%  |
| 1317-65-3  | Calcium Carbonate        | 5.05%  |
| 64742-47-8 | Mineral Spirits          | 3.08%  |
| 1330-20-7  | xylene (mix)             | 1.57%  |

## 4 First-aid measures

**After inhalation:** Supply fresh air; consult doctor in case of complaints.  
**After skin contact:** Remove contaminated clothing. Wash exposed area with soap and water.  
**After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.  
**After swallowing:** Rinse out mouth and then drink plenty of water.  
 Rinse mouth with water. Do not induce vomiting.

**Most important symptoms and effects:** Dizziness  
**Indication of any immediate medical attention needed:** No further relevant information available.

## 5 Fire-fighting measures

**Extinguishing agents:** CO2, extinguishing powder or water spray. Fight larger fires with water spray.  
**Special hazards:** Can form explosive gas-air mixtures.

(Contd. on page 2)  
US4

# Safety Data Sheet

acc. to OSHA HCS

Printing date 10/13/2014

Revised On 10/13/2014

Trade name: WHITE TRAFFIC

(Contd. of page 1)

## Protective equipment for firefighters:

A respiratory protective device may be necessary.

## 6 Accidental release measures

### Personal precautions, protective equipment and emergency procedures:

Use respiratory protective device against the effects of fumes/dust/aerosol.

### Methods and material for containment and cleaning up:

Absorb liquid components with liquid-binding material.

## 7 Handling and storage

### Precautions for safe handling

Use only in well ventilated areas.

### Storage requirements:

Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions. Store locked up.

## 8 Exposure controls/personal protection

### Components with limit values that require monitoring at the workplace:

#### 74-98-6 propane

PEL (USA) Long-term value: 1800 mg/m<sup>3</sup>, 1000 ppmREL (USA) Long-term value: 1800 mg/m<sup>3</sup>, 1000 ppm

TLV (USA) refer to Appendix F

#### 106-97-8 n-butane

REL (USA) Long-term value: 1900 mg/m<sup>3</sup>, 800 ppmTLV (USA) Short-term value: 2370 mg/m<sup>3</sup>, 1000 ppm

#### 7727-43-7 barium sulphate, natural

PEL (USA) Long-term value: 15\* 5\*\* mg/m<sup>3</sup>

\*total dust \*\*respirable fraction

REL (USA) Long-term value: 10\* 5\*\* mg/m<sup>3</sup>

\*total dust \*\*respirable fraction

TLV (USA) Long-term value: 5\* mg/m<sup>3</sup>

\*inhalable fraction; E

#### 1330-20-7 xylene (mix)

PEL (USA) Long-term value: 435 mg/m<sup>3</sup>, 100 ppmREL (USA) Short-term value: 655 mg/m<sup>3</sup>, 150 ppmLong-term value: 435 mg/m<sup>3</sup>, 100 ppmTLV (USA) Short-term value: 651 mg/m<sup>3</sup>, 150 ppmLong-term value: 434 mg/m<sup>3</sup>, 100 ppm

BEI

### Ingredients with biological limit values:

#### 1330-20-7 xylene (mix)

BEI (USA) 1.5 g/g creatinine

Medium: urine

Time: end of shift

Parameter: Methylhippuric acids

### Hygienic protection:

Wash hands after use.

Do not eat or drink while working.

### Breathing equipment:

A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygiene.

### Hand protection:

Protective gloves. The glove material must be impermeable and resistant to the substance.

### Eye protection:

Tightly sealed goggles

## 9 Physical and chemical properties

### Appearance:

Aerosol.

### Odor:

Aromatic

### Odor threshold:

Not determined.

### pH-value:

Not determined.

### Melting point/Melting range

Undetermined.

### Boiling point:

-44 °C (-47 °F)

### Flash point:

-19 °C (-2 °F)

### Flammability (solid, gas):

Extremely flammable.

### Decomposition temperature:

Not determined.

### Auto igniting:

Product is not self-igniting.

### Danger of explosion:

In use, may form flammable/explosive vapour-air mixture.

### Lower Explosion Limit:

1.7 Vol %

### Upper Explosion Limit:

10.9 Vol %

### Vapor pressure:

Not determined.

### Relative Density:

Between 0.77 and 0.85 (Water equals 1.00)

### Vapour density

Not determined.

(Contd. on page 3)

US4

# Safety Data Sheet

acc. to OSHA HCS

Printing date 10/13/2014

Revised On 10/13/2014

Trade name: WHITE TRAFFIC

(Contd. of page 2)

**Evaporation rate** Not applicable.  
**Partition coefficient: n-octonal/water:** Not determined.  
**Solubility:** Not determined.  
**Viscosity:** Not determined.  
**VOC content:** 535.2 g/l / 4.47 lb/gl  
**VOC content (less exempt solvents):** 50.5 %  
**Water:** 18.0 %  
**MIR Value:** 0.63  
**Solids content:** 30.2 %

## 10 Stability and reactivity

**Reactivity:** Stable at normal temperatures.  
**Conditions to avoid:** Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing temperatures.  
**Chemical stability:** Not fully evaluated.  
**Possibility of hazardous reactions:** No dangerous reactions known.  
**Incompatible materials:** No further relevant information available.  
**Hazardous decomposition:** No dangerous decomposition products known.

## 11 Toxicological information

### LD/LC50 values that are relevant for classification:

#### 13463-67-7 titanium dioxide

|            |          |                    |
|------------|----------|--------------------|
| Oral       | LD50     | >20000 mg/kg (rat) |
| Dermal     | LD50     | >10000 mg/kg (rbt) |
| Inhalative | LC50/4 h | >6.82 mg/l (rat)   |

#### 106-97-8 n-butane

|            |          |                |
|------------|----------|----------------|
| Inhalative | LC50/4 h | 658 mg/l (rat) |
|------------|----------|----------------|

#### 1330-20-7 xylene (mix)

|            |          |                  |
|------------|----------|------------------|
| Oral       | LD50     | 8700 mg/kg (rat) |
| Dermal     | LD50     | 2000 mg/kg (rbt) |
| Inhalative | LC50/4 h | 6350 mg/l (rat)  |

**Information on toxicological effects:** No data available.  
**Sensitization:** No sensitizing effects known.

### Carcinogenic categories

#### IARC (International Agency for Research on Cancer)

|            |                  |    |
|------------|------------------|----|
| 13463-67-7 | titanium dioxide | 2B |
| 1330-20-7  | xylene (mix)     | 3  |

#### NTP (National Toxicology Program)

None of the ingredients is listed.

#### OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

## 12 Ecological information

**Aquatic toxicity:** Hazardous for water, do not empty into drains.  
**Persistence and degradability:** The product is degradable after prolonged exposure to natural weathering processes.  
**Bioaccumulative potential:** No further relevant information available.  
**Mobility in soil:** No further relevant information available.  
**Other adverse effects:** No further relevant information available.

## 13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.  
**Recommendation:** Completely empty cans should be recycled.

## 14 Transport information

**UN-Number** UN1950  
**DOT** Aerosols, flammable  
**ADR** 1950 Aerosols  
**Transport hazard class(es):**  
**Class** 2.1  
**Marine pollutant:** No  
**Special precautions for user:** Warning: Gases  
**EMS Number:** F-D,S-U  
**Packaging Group:** --  
**UN "Model Regulation":** UN1950, Aerosols, 2.1

US4

(Contd. on page 4)

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 10/13/2014

Revised On 10/13/2014

**Trade name: WHITE TRAFFIC**

(Contd. of page 3)

**15 Regulatory information****SARA Section 355 (extremely hazardous substances):**

None of the ingredients in this product are listed.

**SARA Section 313 (Specific toxic chemical listings):**

7727-43-7 barium sulphate, natural

1330-20-7 xylene (mix)

**CPSC:** This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.**California Proposition 65 chemicals known to cause cancer:**

13463-67-7 titanium dioxide

100-41-4 ethyl benzene

**EPA:**

7727-43-7 barium sulphate, natural

D, CBD(inh), NL(oral)

1330-20-7 xylene (mix)

I

**16 Other information****Contact:** Regulatory Affairs

US4